

INSTALLATION INSTRUCTIONS for  
Galley, Stove & Sink Acc'y  
(333-930)

STEP 1. Locate track part #844352 in ctr. of inner liner groove, starting from the front. Install end jib track part #25389 w/A 1" P.H. O.H. Sht. Mtl. Scr. #31430; then install the remaining track w/the same 1" P.H. O.H. Sht. Mtl. screws.

STEP 2. Remove the two foremost screws on the track, then raise the fwd. end of track in order to be able to slide at a 90° angle the aft end of galley assy. #815803 onto track. Then swing galley around to onto track. Then swing galley around to a normal position and slide other end of galley pushing it backwards, at which time you will replace removed screws #31430.

STEP 3. To install drain receptacle part #815810, drill a 3" dia. hole per dimensions given on instruction sheet #13707 view "A". Then connect drain tube #828662 to drain receptacle w/clamp #23153. After doing this insert the drain receptacle w/the drain tube pointing to the bowl. Tie-down same with (4) 31723 · 1/8" dia. 4-6 pop rivets.

STEP 4. Assemble the straight gate valve #25387. Elbow #26421 & adapter hose #25388 to the drain tubes #828662 & #828752 w/clamps #23153. Fasten the open end of the drain tube #828752 to the connector thru hull fitting #24455 w/a clamp #23153.

NOTE: For the location of the connector thru hull fitting on the hull - see instruction sheet #13707 view "B".